

USB 2.0 Hub



7-Port USB 2.0 Hub, Up to 480Mbps Speed

The DUB-H7 is a 7-port Universal Serial Bus USB 2.0 hub that allows you to connect up to 7 USB 2.0 peripherals and devices to your USB 2.0 ready PC or iMac. Providing an out of the box industry standard bus, this pocket-sized device expands your PC and Mac by adding 7 USB 2.0 ports to your system.

Seamless Connections

The DUB-H7 is designed to provide quick and easy access to the 7 Type A downstream ports to connect to peripherals with USB 2.0 support, other USB hubs and devices. A single Type B upstream port is provided to connect to the host computer, or another USB hub. Configured directly by the operating system, the DUB-H7 operates seamlessly with both Microsoft's OpenHCI, Intel's Universal HCI and USB 2.0 new generation specification EHCI.

Low, Full and High Speeds Supported with Data Buffering

As a standard USB hub, it buffers USB data from any attached peripherals or devices in compliance with USB specification versions 1.1 and 2.0 to provide an

invisible extension of the USB bus. Supporting both low-speed 1.5Mbps devices, full-speed 12Mbps devices and high-speed 480Mbps, each port creates a bridge between the peripheral and host computer.

Feature-Rich and Easy to Use

Diagnostic LED's are mounted on the device to provide the user with power state and port status. The DUB-H7 is packaged with a 6-foot USB 2.0 A-to-B cable, and a DC 5V/3A external power supply.

Key Features

- USB 2.0 standard
- 7 Type A ports
- 1 Type B port
- Backward compatible with USB 1.1
- Pocket-sized, lightweight

- Diagnostic LEDs provided
- Connects to AC power source through an external AC power adapter
- USB-IF certified

DUB-H7 **Technical Specifications**

Standards

- USB Specification version 1.1
- USB Specification version 2.0 - OHCI
- UHIC
- EHCI

Number of Ports

- 1 upstream USB Type B port
- 7 downstream USB Type A ports

Dimensions

104 mm (L) x 63 mm (W) x 29 mm (H)

Connectivity Rules

- 5 cascaded hubs maximum
- 5 m maximum between each hub
- Up to 127 devices

O.S. Support

- Windows 98SE, ME, 2000, XP (for USB 2.0)
- MacOS X 10.1 and above (for USB 2.0)
- MacOS 8.6 and above (for USB 1.1 only)

EMI Certifications

- FCC Class B
- CE Class B
- C-Tick

Package Includes

USB 2.0 A-to-B cable



USB 2.0 Supported Devices



Ordering Information

DUB-H7

7-port USB 2.0 hub

TEL:

TEL:

TEL:

TEL:

TEL:

TEL:

TEL:

TEL:

TEL:

TEL: TEL

TEL:

Please specify your order as follows:

DUB-H7/A	
DUB-H7/B	
DUB-H7/E	
DUB-H7/CN	
DUB-H7/N	

Includes a US standard AC power adapter Includes a UK standard AC power adapter Includes an EU standard AC power adapter Includes a China standard AC power adapter Includes an Australia standard AC power adapter

Link

Specifications subject to change without D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A Canada Europe Germany France Benelux Italy Iberia Sweden Norway Denmark Finland Singapore Australia Japan . China India Middle East Turkey Chile Brasil South Africa Russia Taiwan

D-Link Corp.

: 1-949-788-0805	FAX: 1-949-753-7033
: 1-905-8295033	FAX: 1-905-8295095
: 44-20-8731-5555	FAX: 44-20-8731-5511
: 49-6196-77990	FAX: 49-6196-7799300
: 33-1-30238688	FAX: 33-1-30238689
: 31-10-2045740	FAX: 31-10-2045880
: 39-2-2900-0676	FAX: 39-2-2900-1723
: 34-93-4090770	FAX: 34-93-4910795
: 46-(0)8564-61900	FAX: 46-(0)8564-61901
: 47-22-309075	FAX: 47-22-309085
: 45-43-969040	FAX: 45-43-424347
: 358-9-2707-5080	FAX: 358-9-2707-5081
: 65-6774-6233	FAX: 65-6774-6322
: 61-2-8899-1800	FAX: 61-2-8899-1868
: 81-3-5434-9678	FAX: 81-3-5434-9868
: 86-10-8518-2533	FAX: 86-10-8518-2250
: 91-22-652-6696	FAX: 91-22-652-8914
: 9714-8834234	FAX: 9714-8834394
: 90-212-335-2553	FAX:90-212-335-2500
: 56-2-232-3185	FAX: 56-2-232-0923
: 55-11-3094-2910	FAX: 55-11-3094-2921
: 27(0)1266-52165	FAX: 27(0)1266-52186
: 7-095-737-3389	FAX: 7-095-737-3390
: 886-2-2910-2626	FAX: 886-2-2910-1515
: 886-2-2916-1600	FAX: 886-2-2914-6299



USB 2.0 Hub